

## NRG Greenboard CR | EPS BATTEN SYSTEM | Table 1.0

NRG Batten System has been designed to compliment the NRG 75mm and the NRG 60mm Cavity Release Series. Post installation of Building paper and Window / Door joinery.... Simply fix NRG selected EPS Battens in accordance with Table 1.0 below.

**PLEASE NOTE:**

1. 2.5 Lm of NRG Batten per / m2 of exterior wall.
2. Simply fix to all existing frame members (studs/plate heads/sills)
3. Ensure correct procedural steps are carried out as per NRG-CR PDF sections details

SELECT NRG GREENBOARD	NRG EPS BATTENS		TOTAL NRG + FIXINGS		NRG CR PVC STARTER BEAD
	SIZE	FIXING	TOTAL mm	FIXING	
NRG 75mm	35mm x 25mm x 1.2m -BOX 98 pcs/117Lm	GALVANISED CLOUT <b>40mm</b> @ <b>400mm Centers</b>	<b>100mm</b>	TIMBER - 130mm STEEL - 125mm DRILL POINT	<b>100mm</b> WEEP HOLE
<b>PLEASE NOTE!</b>	<b>BATTEN:</b> Calculate approx. 2.5 Lm /per m2 of Exterior Wall.	<b>STEEL FRAME:</b> 40mm Drillpoint Button Head Screws			<b>NOTE:</b> NRG specifically designed Weep Hole Starter Bead only to be used.

**Free Call 1800 674 001**

**FOR FURTHER INFORMATION CONTACT NRG HEAD OFFICE**

Unit 4, 32-38 Dover Dr. West Burleigh QLD 4220

Phone. 07 5535 3111 Fax. 07. 5535 3222

email. sales@nrggreenboard.com www.nrggreenboard.com